

AMENDED CLAIMS

Received by the International Bureau 10 May 2004 (10.05.2004);
Original claims 1-16 replaced by amended claims 1-20.

1. Measuring equipment (4) for forming a measured value (V_u)
for voltage representing an ac voltage (U) on a high-voltage
5 conductor (1), said measuring equipment comprising capacitor
equipment (C41) with a known capacitance for connection be-
tween the high-voltage conductor (1) and ground potential
(E), **characterized** in that the measuring equipment further
comprises current-measuring means (41) for sensing a capaci-
10 tor current (I_c) flowing through the capacitor equipment and
for forming the measured value for voltage in dependence on
said capacitor current.
2. Measuring equipment according to claim 1, **characterized**
15 in that said current-measuring means comprises a resistor
(R41) for connection in series with the capacitor equipment,
the measured value for voltage (V_u) being formed in depen-
dence on a sensed voltage across the resistor representing
the capacitor current.
- 20 3. Measuring equipment according to claims 1 and 2,
characterized in that said current-measuring means comprises
a digital/optical measurement value transformer (43) for
transforming the measured value for voltage into a series of
25 light pulses (O1) representing the measured value for vol-
ta-ge.
4. Measuring equipment according to any of claims 1-3,
characterized in that the capacitor equipment is in the form
30 of a coupling capacitor (C) with an external voltage
terminal (B41), that the measuring equipment comprises a
screen (PS) of an electrically conductive material
surrounding said external voltage terminal, that the
measuring equipment further comprises current-measuring
35 means (41) for sensing a capacitor current (I_c) flowing

through the coupling capacitor and for forming the measured value for voltage in dependence on said capacitor current.

5. Measuring equipment according to claim 4, **characterized** in that the capacitor equipment is arranged in a support insulator, and that said electrically conductive screen is electrically conductively connected to the casing (N) of the support insulator.
- 10 6. Measuring equipment according to any of claims 1-3, **characterized** in that the capacitor equipment is in the form of a coupling capacitor (C) with an external voltage terminal (B41), that the capacitor equipment is arranged in a support insulator, that the measuring equipment comprises
15 a screen (PS) of an electrically conductive material surrounding said external voltage terminal, and that said electrically conductive screen is electrically conductively connected to the casing (N) of the support insulator.
- 20 7. Measuring equipment according to any of claims 1-6, **characterized** in that said resistor is connected between the high-voltage conductor and said external voltage terminal on the capacitor equipment and that, in addition thereto, it comprises current-measuring means (42a, 42b) for forming a
25 measured value for current (Va, Vw) representing a line current (I) flowing through the high-voltage conductor.
8. Measuring equipment according to any of claims 1-7, **characterized** in that the measured value for current is
30 supplied to said digital/optical measurement value transformer for transforming the measured value for current into a series of light pulses (O1) representing the measured value for current.
- 35 9. Measuring equipment according to any of claims 1-8, **characterized** in that the digital/optical measurement value

transformer is arranged to sequentially transform said measured value for voltage and said measured value for current into series of light pulses for sequential transmission to ground potential on a common optical transmission link.

5

10. Measuring equipment according any of claims 7-9, **characterized** in that said current-measuring means are mounted on the top of said support insulator, and that said electrically conductive screen is electrically conductively connected to the casing (N) of the support insulator as well as to an electrically conductive part (M) on the current-measuring means that is located at the potential of the high-voltage conductor but is electrically insulated from the external voltage terminal of the coupling capacitor.

15

11. A method for forming at least one measured value (V_u) for voltage, representing an ac voltage (U) on a high-voltage conductor (1), wherein measuring equipment comprising capacitor equipment (C41) with a known capacitance is connected between the high-voltage conductor (1) and ground potential (E), **characterized** in that a capacitor current (I_c) flowing through the capacitor equipment is sensed and that said measured value for voltage is formed in dependence on said capacitor current.

20

12. A method according to claim 11, **characterized** in that a resistor (R41) is connected in series with the high-voltage conductor and the capacitor equipment and that said capacitor current (I_c) is sensed as a measured value (V_u) for voltage across the resistor.

25

13. A method according to any of claims 11 and 12, **characterized** in that the measured value for voltage is supplied to a digital/optical measurement value transformer and that said the measured value for voltage is transformed into a series of light pulses (01) representing the measured value for voltage.

30

14. A method according to any of claims 11-13, **characterized**
in that the capacitor equipment is constituted by a coupling
capacitor (C), in that the coupling capacitor is provided
with an external voltage terminal (B41), that the coupling
5 capacitor is arranged in a support insulator (N), and that
said measuring equipment is provided with a screen (PS) of
an electrically conductive material, surrounding said
external voltage terminal, that a capacitor current (Ic)
flowing through the capacitor equipment is sensed and that
10 said measured value for voltage is formed in dependence on
said capacitor current.

15. A method according to claim 14, **characterized** in that
the capacitor equipment is arranged in a support insulator
15 (N), and that the screen is electrically conductively
connected to the casing (N) of the support insulator

16. A method according to any of claims 11-13, wherein the
capacitor equipment is constituted by a coupling capacitor
20 (C), **characterized** in that the coupling capacitor is provi-
ded with an external voltage terminal (B41), that the capa-
citor equipment is arranged in a support insulator (N), and
that said measuring equipment is provided with a screen (PS)
of an electrically conductive material, surrounding said
25 external voltage terminal and being electrically conducti-
vely connected to the casing (N) of the support insulator.

17. A method according to any of claims 11-16, **characterized**
in that said resistor (R41) is connected between the high-
30 voltage conductor and said external voltage terminal on the
capacitor equipment, and that, in addition thereto, a
current-measuring means (42a, 42b) is connected to the
measuring equipment, and that a measured value (Va, Vw) for
current, representing a line current (I) flowing through the
35 high-voltage conductor, is sensed.

18. A method according to any of claims 11-17, **characterized**
in that the measured value for current is supplied to a

digital/optical measurement value transformer, and that said measured value for current is transformed into a series of light pulses (O1) representing the measured value for current.

5

19. A method according to any of claims 11-18, **characterized** in that said measured value for voltage and said measured value for current are transmitted sequentially to ground potential on a common optical transmission link.

10

20. A method according to any of claims 11-19, **characterized** in that said current-measuring means is mounted on the top of said support insulator, and that said electrically conductive screen is electrically conductively connected to an electrically conductive part (M) on the current-measuring means that is located at the potential of the high-voltage conductor but is electrically insulated from the external voltage terminal of the coupling capacitor, as well as to the casing (N) of the support insulator.

20